## **Power Operated Hydraulic Press Machine**









10 TON CAPACITY

100 TON CAPACITY

LIGHT DUTY MODEL

SIMPLE OPERATION: Press is provided with motorized pump unit and hand operated control valve, Pump is driven by flange coupled motor and has a pressure adjusting valve for adjusment of high pressure.

HIGH QUALITY HYDRAULIC UNIT: Cylinder is made of special Steel secures absolute pressure tightness. The seals are made of special material an guarantee long life. PISTON ROD & PISTON HEAD are carefully ground and hard chrome plated to obtain closest accuracy in grinding.

PRECISION PRESSING: Actual pressure may be read in tons from the precision pressure gauge that has red Zone from maximum pressure and upwards. To protect pressure gauge during press work, a cut off valve is inserted near the gauge. Press beds are planed off and as standard equipment 2 PLANED OFF STRAIGHTEN V BLOCKS are supplied.

For Power Operated Hydraulic press, Spring Holdup for the Ram is provided at extra cost.

## **SPECIFICATION**

## Type of Models:

- 1) Hand Lever Operated- H-Frame
- 2) PLC Control Panel Operated- H-Frame

## > Standard Accessories :

- 1.) Variable Stroke Adjustment With Limit
- 2.) Pressure reversal hydraulic switches
- 3.) Front Operator Control Box
- 4.) Stroke Counter

	Tons	Between Column Length x Width	Between Ram to bed Min. Max.	Travel Of Ram	Motor Power
		mm. mm.	mm. mm.	mm.	H.P.
	15	650 x 150	75 x 600	150	3
	20	700 x 225	150 x 750	150	3
	25	850 x 300	180 x 910	180	5
	40	950 x 350	180 x 910	190	5
	50	1000 x 400	180 x 950	200	5
	60	1050 x 450	180 x 975	200	5
	75	1150 x 500	180 x 975	210	7.5
	100	1200 x 600	180 x 975	225	7.5
	150	1300 x 635	180 x 975	240	10
	200	1325 x 650	180 x 975	240	10
	250	1350 x 650	180 x 975	250	20
	300	1395 x 660	180 x 975	265	20
	500	1425 x 685	180 x 975	300	25