


Gantry type CNC Drilling Machine



SPECIFICATION

Model	TLP-PD 2016	TLP-PD 2016/2	TLP-PD 3016	TLP-PD 3016/2
Processing Scope (mm)	2000x1600	2000x1600	3000x1600	3000x1600
Stack Thickness (mm)	100			
Spindle Number	1	2	1	2
Spindle Model	Morse 4 # Taper Hole			
Spindle Rotating Speed (r/min)	120-560			
Feed Motor	Hydraulic Automatic Stroke Drilling Power Head			
Feed Stock (mm)	180			
Drilling Diameter (mm)	12-5 (12-63 optional)			
Main Motor Power (kW)	5.5/7.5 (optional)	5.5x2/7.5x2 (optional)	5.5/7.5 (optional)	5.5x2/7.5x2 (optional)
Drilling Precision (mm)	± 0.5			
Re-positioning Precision (mm)	± 0.2			
Number Of Clamping Cylinders	12			
Clamping Force (kN)	7.5			
Clamping System	Double Side Button Control of Gantry			
Hydraulic Pump Pressure (Mpa)	6			
Control System	PLC+IPC			
Size	3500x2650x2870 mm			

High Speed Gantry type CNC Drilling Machine

SPECIFICATION

Model		TLP-PHD 1616	TLP-PHD 2016	TLP-PHD 2020
Processing Range	LxW (mm)	1600x1600	2000x1600	2000x2000
	Thickness (mm)	15-100		
Processing Range	Number of spindle	1		
	Spindle Model	BT40/BT50		
	Spindle Speed (r/min)	30-4500		
	Feed Stroke (mm)	260		
	Tapping Diameter (mm)	M20		
Motor Power (kW)	Spindle Servo Motor	7.5/11		
	X Axis	2x2.3		
	Y Axis	2.3		
	Z Axis	2.3		
Positioning Accuracy (mm)		0.1		
Repeatable Positioning Accuracy (mm)		0.08		
Control Mode		Siemens 808D CNC System/PLC + upper computer		
Weight (T)		5.5	6.6	7.2
Dimension (mm)		3800x2050x2750	4200x2450x2750	4200x2850x2750



Application:

