

Hand Operated Hydraulic Press Machine



15 TON CAPACITY



100 TON CAPACITY

The sturdy construction of all presses guarantees stability and durability. The press is provided with a 2-stage hand pump. The low pressure pump is used for rapid advance of piston at low pressure. The high pressure pump is provided with a special material lining and is used for slow advance at high pressure.

The winch provided for raising and lowering the table is smooth running. During operation, the table is fastened by means of pins. The press has been all steel welded.

STANDARD ACCESSORIES: Pressure gauge, Planed off V-Blocks for Straightening.

APPLICATION: Used for Bending, Axle Straightening, Carbide die Pressing.

SPECIFICATION



MINI JACK TYPE HYDRAULIC PRESS
5 TON & 10 TON MODEL'S AVAILABLE

Tons	Between Column Length x Width mm. mm.	Between Ram to bed Min. Max. mm. mm.	Travel Of Ram mm.
5	500 x 125	75 x 600	100
10	600 x 150	75 x 600	125
15	650 x 150	75 x 600	150
25	850 x 300	180 x 910	180
40	950 x 350	180 x 910	190
50	1000 x 400	180 x 950	200
60	1050 x 450	180 x 975	200
75	1150 x 500	180 x 975	210
100	1200 x 600	180 x 975	225
150	1300 x 635	180 x 975	240