

Pillar Drill Machine



PS40



PS25



PS20



Non Gear Pillar Drill Machine
Capacity 40 mm
DS 40



All Geared, Auto Feed
Pillar Drill Models
Available in 40 MM & 50 MM
PAG 40

Standard Accessories

- ▶ Motor Pulley
- ▶ Tapper Drift
- ▶ Handles

Optional Accessories

- ▶ Electric Motor
- ▶ R & F Switch
- ▶ Drill Chuck
- ▶ Arbour
- ▶ Coolant Pump with tank
- ▶ Machine Lamp

Model No.	PS-40	PS-25	PS-20
Titling working table	FIXED	FIXED	FIXED
Drilling capacity	40 mm	25 mm	20 mm
Pillar Diameter	121 mm	92 mm	74.30 mm
Spindle nose to table distance	595 mm	660 mm	660 mm
Distance from spindle nose to base distance	1050 mm	1050 mm	900 mm
Distance from spindle centre to pillar surface (in mm)	320 (Max)	250 (Max)	200 (Max)
Table Travel	480 mm	480 mm	200 mm
Taper in Spindle	MT-4	MT-3	MT-2
Number of Speed	8 sped	8 sped	8 sped
Range of Speed (RPM)	70 to 2000	130 to 2600	87 to 3224
Table Size (in mm)	410 x 410	330 x 330	260 x 260
Base Size (m/c area in mm)	440 x 715	365 x 575	480 x 300
Overall base size (in mm)	445 x 720	370 x 580	490 x 310
Spindle Travel	250 mm	180 mm	130 mm
Pillar Length	1450 mm	1410 mm	1170 mm
Overall height with pulley guard	1860 mm	1730 mm	1420 mm
V-Bell sction	B-59	B-52"	A-42
Weight (Approx)	325 Kgs	225 Kgs	100 kgs
Motor 1440 RPM 3 Phase 440 Volts	2 H.P	1 H.P	1 H.P
Shipping Wooden Case	860x460x	850x450x	660x380x
Inner SizeLxWxH	1580 m	1770 mm	1440 mm