



Valve Refacer



Model	PVR-150
Valve Stem Capacity	4.50 to 17.00 mm
Valve Angle Adjustment	0 to 90 degrees
Valve Head Capacity	up to 90 mm
Grinding Wheel Size	5" x 1/2" x 5/8"
Butt Grinding Wheel	4" x 3/4" x 5/8"
Grinding Wheel Spindle Speed	4000 rpm
Work Head Spindle Speed	175 rpm
Motor	0.5 HP
Net / Gross Weight	100 / 125 kg
Shipping Dimensions	760 x 510 x 590 mm
Shipping Volume	0.25 m3

Connecting Rod Boring Machine



Model	ARB 500
Minimum And Maximum Bore Centre Of Con-Rod	Min 80 – Max 600 mm
Boring Spindle Speeds (Variable - VFD)	Infinitely variable, 100-1600 rpm
Boring Range	Min ϕ 15 – Max ϕ 175
Feed Both Direction	Infinitely Variable
Table Traverse - Crosswise	50 mm
Table Movement - Longitudinal	450 mm
Spindle Speed Motor	1 HP 3PH 50 Hz
Motor Table Feed (Variable Drive - VFD)	0.5HP 3PH 50 Hz
Length Of The Machine	1200mm
Width Of The Machine	650mm
Height Of The Machine	2000mm
Net Weight	750kg (approx)
Gross Weight	900kg (approx)
Shipping Volume	3 m3