

Hydraulic Hose Crimping Machine







	Crimping Range	6~51mm (1/4"~2")
P.	Quantity of Mold	10 Sets with long dies 15,18,23,26 (70mm) 31,36,41 (100 mm) 47,55 (100 mm) 61 (80mm)
ole	Accuracy	0.01mm
ne l	Swept Volume	2.5L/5L (Optional)
	System Pressure	31.5Mpa
	Power	3KW
	Voltage	220V 50HZ Single Phase
	Buckling Pressure	500T
	Oil quantity	40L
	Efficiency	200pcs/h
	Dimension	800*630*1300 mm
	Package Dimension	890*710*1430mm
	Net Weight	310kg
	Gross Weight	320kg
	Maximum Open Diameter	114mm
	Range	± 30mm
8.5	Tilting head included Colour full Foot Pec	body-yellow, the rest-black, the head-orange dal and light included

Specification





IndieCrimp - Slim

Spec	cification
Crimping Range	6~76mm (1/4"~3") 4SP
Quantity of Mold	15 Sets 14 18 22 26 30 34 39 45 50 55 65 75 85 92 master die length 80mm-85mm
Accuracy	0.01mm
Swept Volume	10L Output of pump 14L/min
System Pressure	31.5Mpa
Power	4KW
Voltage	380V 50HZ 3Phase
Buckling Pressure	800T
Oil quantity	110L
Efficiency	250pcs/h
Stroke time	14+35
Package Dimension	730*1040*1600mm=1.2CBM
Weight	1300kg
Maximum Open Diameter without dies	170mm
Range	± 60mm
Light: included Foot pedal: included	Quick change tool included

	60.	00	
6			Name of the last
		OF STREET	
6			TA

IndieCrimp - Vishal

Specification			
rimping Range	6~102mm		
ree Dies	17 Sets incl		
Accuracy	0.01mm		
olume of oil tank	10L		
ystem Pressure	31.5MPa		
Notor Power (as your requirements)	4kW		
oltage (as your requirements)	380V 50HZ 3Phase		
uckling Pressure	2100T		
fficiency	200pcs/h		
Naximum Open Diameter	200mm		
he max open tolerance	± 30mm		
ontrol system	Electric Automatic		
ontrol system	Micro control with Button control with		
lydraulic oil	46 L		
let Weight	500kg		
iross Weigh	520kg		
Machine Dimension (mm)	890*570*1200		
ackage Dimension(mm)	910*590*1210=0.66CBM		
oot Pedal and light	included		