

DRILLING CUM MILLING MACHINE



STANDARD ACCESSORIES

- ◆ Tie Rod
- ◆ Auto - Tapping Electrical
- ◆ Coolant System
- ◆ Milling Set
- ◆ Working Lamp

OPTIONAL ACCESSORIES

- ◆ Drill Chuck
- ◆ Clamping Kit (58 Pcs.)
- ◆ Rotary Table
- ◆ DRO System
2 Axis & 3 Axis DRO



SPACIFICATION

| | |
|--|----------------|
| Drilling Capacity | 45 MM |
| Face Milling Capacity | 080 MM |
| End Milling Capacity | 32 MM |
| Tapping Capacity | 04 MM to 20 MM |
| Distance : Spindle Nose to Table | 450 MM |
| Min. Distance : Spindle Axis to Column | 260 MM |
| Spindle Travel | 130 MM |
| Spindle Taper | MT 4 |
| Step of Spindle Speed | 6 |
| Range of Spindle Speed 50Hz | 80 - 1250 RPM |
| Swivel Angle of Head Stock Vertically | ±90° |
| Table Size | 800 x 240 MM |
| Forward & backward Travel of Table | 200 MM |
| Left & Right Travel of Table | 500 MM |
| Motor Power | 1.50 KW 2 HP |
| Net Weight / Gross Weight | 450 Kg |



HEAD OFFICE :

PATHAK INDUSTRIES KOL

a unit of T.L. PATHAK GROUP

116,117,G.T. ROAD,SALKIA,HOWRAH-711106



8895929247



info@pathak.in



www.tlpathakgroup.com